



This Fall Protection Plan will be used while operating aerial lifts and MEWP's

Jobsite: _____

Foreman: _____ **Phone Number:** _____

Superintendent: _____ **Phone Number:** _____

Safety: _____ **Phone Number:** _____

Users: Any person(s) using fall protection equipment will be required to take a fall protection class within the last (4) years.

Although not required by either ANSI or OSHA, some GC's may require that a full body harness be used with a lanyard attached to an authorized lanyard anchorage point when operating scissor lifts.

Anyone operating a Boom Lift will be required to wear a full body harness used with a lanyard attached to an authorized lanyard anchorage point.

List MEWP/Aerial Lift Equipment that will be used:

List Fall Protection Equipment that will be used:

Describe your proposed plan here:

MEWP/Scissor – Using lift to access work throughout the jobsite. Daily lift inspections will occur prior to work start and kept with the equipment. Workers will identify and mitigate job specific hazards and changes in conditions on daily PTP's.

- Fall Protection equipment will be inspected prior to each use and stored hung up, away from open sparks and out of direct sunlight when not in use.
- While operating the lift the worker will:
 - Keep the platform floor clear of debris.
 - Attach the platform entry chain or close the entry gate before operating.
 - Hit the red dead button unless repositioning.
 - Never leave platform or stand on rails to access work.

Describe Rescue Plan Here: In the event of a fall, partner will engage emergency decent device located on lift to safely lower fallen worker.

Duration this plan will be in effect: _____