

## DAILY SCAFFOLD INSPECTION CHECKLIST

JOB:	MONTH:						
	Mon.	Tue.	Wed.	Thu.	Fri.	Sat.	Sun
DATED:							
•							
That all toe board are sound and secured in proper locaton.							
All guard railing and midrails are secure and in proper location.							
That all side and end brackets are properly secured and in place.							
Weight loads for laminated planks: <u>50lbs/SF (500)</u>							
Weight loads for Douglas Fir planks: <u>25lbs/SF (250)</u>							
UNIQUE ITEMS:							
	DATED: Survey the job site for any disturbances that may have happened to the scaffold when last used. Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed. The uprights (frames) are properly braced, plumb and tied off securely at proper locations. That all horizontal bracing, cross bracing and all bracing is in place and secure. That all planking has been visually inspected for warping, checking and any damaged planks. That all planking has been visually inspected for proper laps and that the planks are securely in place. That all toe board are sound and secured in proper locaton. All guard railing and midrails are secure and in proper location. That all connections are properly pinned, bolted, or secured per manufacturers instructions. That all side and end brackets are properly secured and in place. All access and egress ladders are secure and the steps and rungs are lined up properly. Weight loads for laminated planks: <u>50lbs/SF (500)</u> Weight loads for Douglas Fir planks: <u>25lbs/SF (250)</u> Scaffolding properly tagged prior to use. (i.e.: Canileevered/Stepped Scaffolding, etc) <b>UNIQUE ITEMS:</b>	DATED: Survey the job site for any disturbances that may have happened to the scaffold when last used. Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed. The uprights (frames) are properly braced, plumb and tied off securely at proper locations. That all horizontal bracing, cross bracing and all bracing is in place and secure. That all planking has been visually inspected for warping, checking and any damaged planks. That all planking has been visually inspected for proper laps and that the planks are securely in place. That all toe board are sound and secured in proper location. All guard railing and midrails are secure and in proper location. That all connections are properly pinned, bolted, or secured per manufacturers instructions. That all side and end brackets are properly secured and in place. All access and egress ladders are secure and the steps and rungs are lined up properly. Weight loads for laminated planks: <u>50lbs/SF (500)</u> Weight loads for Douglas Fir planks: <u>25lbs/SF (250)</u> Scaffolding properly tagged prior to use. (i.e.: Canileevered/Stepped Scaffolding, etc) <b>UNIQUE ITEMS:</b>	DATED:       Mon. Tue.         Survey the job site for any disturbances that may have happened to the scaffold when last used.       Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed.         The uprights (frames) are properly braced, plumb and tied off securely at proper locations.       Image: Construct of the secure and the foundations have not been visually inspected for warping, checking and any damaged planks.         That all planking has been visually inspected for proper laps and that the planks are securely in place.       Image: Construct of the secure and in proper location.         All guard railing and midrails are secure and in proper location.       Image: Construct of the secure and in proper location.         That all connections are properly pinned, bolted, or secured per manufacturers instructions.       Image: Construct of the steps and rungs are lined up properly.         Weight loads for laminated planks: <u>50lbs/SF (500)</u> Weight loads for laminated planks: <u>25lbs/SF (250)</u> Scaffolding properly tagged prior to use. (i.e.:       Canileevered/Stepped Scaffolding, etc)         UNIQUE ITEMS:       Image: Construct of the steps and construct of the s	DATED:         Survey the job site for any disturbances that may have happened to the scaffold when last used.         Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed.         The uprights (frames) are properly braced, plumb and tied off securely at proper locations.         That all horizontal bracing, cross bracing and all bracing is in place and secure.         That all planking has been visually inspected for warping, checking and any damaged planks.         That all planking has been visually inspected for proper laps and that the planks are securely in place.         That all connections are properly pinned, bolted, or secured per manufacturers instructions.         That all side and end brackets are properly secured and in place.         All access and egress ladders are secure and the steps and rungs are lined up properly.         Weight loads for Douglas Fir planks: <u>50lbs/SF (500)</u> Weight loads for Douglas Fir planks: <u>50lbs/SF (500)</u> UNIQUE ITEMS:	DATED:         Survey the job site for any disturbances that may have happened to the scaffold when last used.       Mon. Tue. Wed. Thu.         Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed.       Image: Comparison of the uprights (frames) are properly braced, plumb and tied off securely at proper locations.         That all horizontal bracing, cross bracing and all bracing is in place and secure.       Image: Comparison of the uprights (frames) are properly braced for warping, checking and any damaged planks.         That all planking has been visually inspected for proper laps and that the planks are securely in place.       Image: Comparison of the uprights (frames) are properly planed.         All guard railing and midrails are secure and in proper location.       Image: Comparison of the uprights (frames) are properly planed, bolted, or secured per manufacturers instructions.       Image: Comparison of the uprights (frames) and rungs are lined up properly.         Weight loads for Douglas Fir planks:       Solbs/SF (500)       Image: Comparison of the uprights (frames) comparison of the upright (frames) comparison of the uprights (frames	DATED:         Survey the job site for any disturbances that may have happened to the scaffold when last used.         Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed.         The uprights (frames) are properly braced, plumb and tied off securely at proper locations.         That all horizontal bracing, cross bracing and all bracing is in place and secure.         That all planking has been visually inspected for warping, checking and any damaged planks.         That all planking has been visually inspected for proper laps and that the planks are securely in place.         That all connections are properly pinned, bolted, or secured per manufacturers instructions.         That all side and end brackets are properly secured and in place.         All access and egress ladders are secure and the steps and rungs are lined up properly.         Weight loads for Douglas Fir planks:       25lbs/SF (250)         Scaffolding properly tagged prior to use. (i.e.: Canileevered/Stepped Scaffolding, etc)       UNIQUE ITEMS:	DATED: DATED: Survey the job site for any disturbances that may have happened to the scaffold when last used. Scaffold post, screw & base plate are level, secure and the foundations have not been disturbed. The uprights (frames) are properly braced, plumb and tied off securely at proper locations. That all horizontal bracing, cross bracing and all bracing is in place and secure. That all planking has been visually inspected for warping, checking and any damaged planks. That all planking has been visually inspected for proper laps and that the planks are securely in place. That all toe board are sound and secured in proper location. All guard railing and midrails are secure and in proper location. That all side and end brackets are properly secured and in place. All access and egress ladders are secure and the steps and rungs are lined up properly. Weight loads for laminated planks: <u>50lbs/SF (500)</u> Weight loads for Douglas Fir planks: <u>25lbs/SF (250)</u> Scaffolding properly tagged prior to use. (i.e.: Canileevered/Stepped Scaffolding, etc) UNIQUE ITEMS:

 Competent Person:
 Date:

 Superintendent/Foreman:
 Date:

 P = Item Passes Inspection
 C = Correction Required / Estimated Time to Correct

8015 SW Hunziker Rd Tigard, OR 97223 | Phone: (503) 520-9991 | Fax: (503) 626-9891